

CONTOUR (FR) 3X PEGASUS

Approved
Business Development Manager
Doc No: TDS-038 Rev: B
Issue Date: 07/10/2013

DESCRIPTION This is a three-ply laminated product that is designed for outdoor stretch tenting. This product exhibits very good stretch and recovery properties. The product is waterproofed by sandwiching a polyurethane membrane between two knitted fabrics. It is not intended to be a permanent structure, as lengthy exposure to UV and hydrolysis, will eventually compromise the membrane.

BENEFITS

- ✓ Waterproof
- ✓ UV Resistant
- ✓ Water/Oil Repellent
- ✓ Anti-Fungal
- ✓ FR

INTENDED USE Outdoor Stretch Tenting

PROPERTY	UNITS	METHOD	SPEC
Composition	-	COA	Polyester/PU
Construction	-	Visual	Laminated
Weight	gsm	Finlam	750 ±5%
Usable Width	cm	Finlam	150
Water Penetration	mm	SABS SM 99(10 Min Hydrostatic Head)	> 2000
Tensile Strength MachineDirection (Ave)	Newtons	BS 13934	> 1500
Tensile Strength Cross Direction(Ave)	Newtons	BS 13934	> 1200
Average Peelbond MachineDirection (Ave)	Newtons	SANS 1439	> 10
Average Peelbond Cross Direction(Ave)	Newtons	SANS 1439	> 10
Anti-Fungal	-	DIN 53931	Pass
Colour Fastness to Light	Blue Wool	ISO 105-B02	≥ 6
Oil Repellency	Rating	AATCC 118	≥ 4
Water Repellency	Rating	AATCC 22	≥ 80
Flammability Performance	-	DIN 75200	Pass
Flammability Performance	-	BS 7837	Pass

Please note that the information shared in this document is for general information only, and it is the responsibility of the customer to ensure that this product meets their specific requirements. The data in this document is for indication only and the product performance properties may vary. This document is not to be treated as a Certificate of Conformance. Dimensions Tents will not entertain any damages claimed against them as a result of data expressed in this document.